



The **Mink web spreader roller BSW10022** has a total diameter of 104 mm.  
 The steel shaft fully mounted on ball bearings has a diameter of 25 mm h9.  
 Please provide details for overall length, roller length, internal threads and whether you require an electrically conductive or non-conductive version.  
 If the roller length is large or the web tension relatively high, please keep the shaft ends short.

Enquiry:  Quantity: \_\_\_\_\_ unit(s)  
 Order:  For plant: \_\_\_\_\_

Overall length: \_\_\_\_\_ mm  
 Roller length: \_\_\_\_\_ mm

Internal thread: \_\_\_\_\_ M x \_\_\_\_\_ mm Without thread

Conductive version: Yes  No  Optional

**Operating conditions:**

Type of material: Film  Textile  Paper  Tissue  Nonwoven   
 Thickness of material: \_\_\_\_\_ µm or mm  
 Weight: \_\_\_\_\_ g/sqm  
 Web speed: \_\_\_\_\_ m/min  
 Wrap angle: \_\_\_\_\_ °  
 Web width: \_\_\_\_\_ mm  
 Max. temperature: \_\_\_\_\_ °C  
 Web tension: \_\_\_\_\_ N  
 Application: dry  wet

**From:**

|                 |  |
|-----------------|--|
| Company:        |  |
| Contact person: |  |
| Phone / Fax:    |  |
| E-mail:         |  |

**Your contact for Mink web spreader rollers:**

Mink Converting Phone: +49 (0) 7161-4031-0 Fax: +49 (0) 7161-4031-500 Mail: [bsw@mink-buersten.com](mailto:bsw@mink-buersten.com)